



Specificaties	Motor
Voltage	24-240 AC or DC
Looptijd	9 Sec.
Torque Nm	20 Nm
Watt	26,7 bij 24VAC
Verwarming	Heather
Gewicht	1.8 Kgs
Eindschakelaars	2 extra

Kogelkraan HT 3/2 elektrisch met PSI aandrijving type S020

Artikel code	Omschrijving	Bruto prijs:
100 349 032	KKE 032 3/2 + PSI S020 24-240VAC-DC 15sec. epdm	€ 505,95
100 349 040	KKE 040 3/2 + PSI S020 24-240VAC-DC 15sec. epdm	€ 519,55
100 349 050	KKE 050 3/2 + PSI S020 24-240VAC-DC 15sec. epdm	€ 518,35
100 349 063	KKE 063 3/2 + PSI S020 24-240VAC-DC 15sec. epdm	€ 544,00

Série Modelo / Series Model		S20 / B20
Tempo maniobra sin carga / Operation time unload		10 Sec./90°
Par máximo arranque / Maximum torque break		25 Nm / 221 lb/in
Par máximo operacional / Maximum operational torque		20 Nm / 177 lb/in
Tempo bajo tensión / Duty rating		75%
Ángulo máximo de maniobra / Max. Working angle		0° - 270°
Interruptores final de carrera / Limit switch		4 SPSTNO micro (2 motor stop and 2 confirmations)
Resistencia calefactora / Automatic heater		3.5 W
Conector grande / Big Plug		EN175301-803 FORM A
Conector pequeño / Small Plug		DIN43650/C
Grado protección IEC 60529 / Protection IEC 60529 rating		IP67
Temperatura / Temperature		+20°C +70°C -4°F +158°F
Brida ISO 5211 / ISO 5211 Plate		Standard: F03/F04/F05 Opcional: F02 *17mm
Salida dotada cuadrado DIN3337 DIN 3337 Female output drive		Standard: *14mm Opcional: *9, *11mm
Peso / Weight		1.8 Kg

S20 / B20						
Voltage	Unload		Max. Operational Torque 20Nm		Max. Torque Break 25Nm	
	A	W	A	W	A	W
12 VDC	0,75	9,06	1,80	21,60	1,95	23,34
24 VDC	0,45	10,77	0,90	21,49	0,97	23,39
48 VDC	0,21	9,93	0,42	20,38	0,46	22,07
110 VDC	0,07	8,00	0,13	14,30	0,14	15,70
12 VAC	1,04	12,51	1,85	22,18	2,28	27,32
24 VAC	0,59	14,20	1,12	26,77	1,28	30,62
48 VAC	0,34	16,37	0,69	33,16	0,75	36,22
110 VAC	0,14	15,73	0,27	29,52	0,30	32,67
240 VAC	0,10	23,76	0,15	36,43	0,16	39,07